

Re : Preliminary Amendment
Appl. No. : 10/726,797
Filed : December 13, 2003

I. AMENDMENTS TO THE CLAIMS

The following listing of the claims replaces all prior versions and listing of the claims in the application:

1. (Amended) A table comprising:
a plastic table top comprising:
a top portion; ~~surface~~,
a bottom portion; ~~and surface~~,
a pair of spaced apart generally L-shaped brackets extending outwardly from
the bottom portion of the table top, at least a portion of the generally L-shaped
brackets being constructed from plastic and being integrally formed with the table top
as part of a unitary, one-piece structure, surface thereof, the brackets and the bottom
portion surface at least partially defining a chamber;
a drawer that is sized and configured to be slidably disposed in the chamber and
movable between a retracted position and an extended position; and
a pair of legs connected to the table top.
2. (Currently Amended) The table as recited in claim 1, wherein the entire generally L-shaped brackets are formed integrally with the plastic table top.
3. (Currently Amended) The table as recited in claim 1, wherein each generally L-shaped bracket comprises a vertical portion and a horizontal portion formed integrally together.

Re : Preliminary Amendment
Appl. No. : 10/726,797
Filed : December 13, 2003

4. (Currently Amended) The table as recited in claim 1, wherein each generally L-shaped bracket comprises a vertical portion and a discrete horizontal portion attached together.

5. (Currently Amended) The table as recited in claim 4, wherein the horizontal portion is formed by a generally ~~an~~ L-shaped angle iron having a vertical portion and a horizontal portion, the vertical portion of the iron being connected to the vertical portion of the generally L-shaped bracket such that the horizontal portion of the generally L-shaped iron is disposed transversely thereto.

6. (Currently Amended) The table as recited in claim 1, further comprising a generally ~~an~~ L-shaped angle iron disposed in a corner of each generally L-shaped bracket.

7. (Original) The table as recited in claim 1, further comprising a lip formed around at least a portion of the outer periphery of the bottom surface of the table top.

8. (Currently Amended) The table as recited in claim 7, further comprising a notch formed in the lip at the location of the generally L-shaped brackets, the space between the generally L-shaped brackets being substantially the same or less than the length of the notch.

Re : Preliminary Amendment
Appl. No. : 10/726,797
Filed : December 13, 2003

9. (Original) The table as recited in claim 7, further comprising:
- a recess formed around the periphery of the bottom surface of the table top such that the bottom surface is substantially level with the bottom portion of the outer lip; and
- a cross bar attached to an end of each of the table legs, wherein the cross bar is disposed in the recess and pivotally attached to the table top.

Please add the following new claims:

10. (New) The table as recited in claim 1, wherein at least one of the generally L-shaped brackets includes a stop that is sized and configured to restrict the movement of the drawer within the chamber.
11. (New) The table as recited in claim 1, wherein at least a portion of the generally L-shaped brackets form at least a portion of a base and at least a portion of the base is sized and configured to support the drawer.

Re : Preliminary Amendment
Appl. No. : 10/726,797
Filed : December 13, 2003

12. (New) A table comprising:

a table top constructed from blow-molded plastic, the table top including an upper portion, a lower portion and a hollow interior portion formed during the blow-molding process;

a drawer movable between a retracted position and an extended position relative to the table top;

one or more receiving portions integrally formed in the table top as part of a unitary, one-piece structure, the receiving portions including a hollow interior portion that is formed during the blow-molding process, the receiving portions being sized and configured to receive at least a portion of the drawer and allow the drawer to move between the retracted position and the extended position; and

one or more legs that are sized and configured to support the table top above a surface.

13. (New) The table as recited in claim 12, wherein the one or more receiving portions form at least a portion of a base and at least a portion of the base is sized and configured to support the drawer.

14. (New) The table as recited in claim 12, wherein each of the one or more receiving portions include at least one lateral portion.

Re : Preliminary Amendment
Appl. No. : 10/726,797
Filed : December 13, 2003

15. (New) The table as recited in claim 12, wherein each of the one or more receiving portions includes at least one bottom portion.

16. (New) The table as recited in claim 12, wherein each of the one or more receiving portions includes at least one lateral portion and at least one bottom portion.

17. (New) The table as recited in claim 16, wherein the at least one lateral portion and the at least one bottom portion include a hollow interior portion that is integrally formed with the table top as part of a unitary, one-piece construction during the blow-molding process.

18. (New) The table as recited in claim 16, further comprising one or more brackets attached to the one or more receiving portions.

19. (New) The table as recited in claim 12, further comprising one or more brackets attached to the one or more receiving portions.

Re : Preliminary Amendment
Appl. No. : 10/726,797
Filed : December 13, 2003

20. (New) A table comprising:

a table top constructed from blow-molded plastic and including an upper portion, a lower portion and a hollow interior portion that is formed during the blow-molding process;

one or more legs connected to the table top;

a drawer movable between a retracted position and an extended position relative to the table top;

a first generally L-shaped bracket extending outwardly from the bottom portion of the table top, the first generally L-shaped bracket being integrally formed with the table top as part of a unitary, one-piece structure, the first generally L-shaped bracket including a hollow interior portion that is formed during the blow-molding process, the first generally L-shaped bracket including a lateral portion and a bottom portion, the first generally L-shaped bracket being sized and configured to allow the drawer to move between the retracted position and the extended position; and

a second generally L-shaped bracket extending outwardly from the bottom portion of the table top, the second generally L-shaped bracket being integrally formed with the table top as part of a unitary, one-piece structure, the second generally L-shaped bracket including a hollow interior portion that is formed during the blow-molding process, the second generally L-shaped bracket including a lateral portion and a bottom portion, the second generally L-shaped bracket being sized and configured to allow the drawer to move between the retracted position and the extended position.